




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04N 7/18, G08B 13/196		A1	(11) International Publication Number: WO 99/59340
			(43) International Publication Date: 18 November 1999 (18.11.99)
(21) International Application Number: PCT/IB99/00777		(81) Designated States: BR, JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 29 April 1999 (29.04.99)			
(30) Priority Data: 98201510.9 8 May 1998 (08.05.98) EP		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).			
(71) Applicant (for SE only): PHILIPS AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE).			
(72) Inventors: VAN RAVENSTEIN, Peter, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VISSCHERS, Christiaan, C., M.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).			
(74) Agent: STEENBEEK, Leonardus, J.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).			

(54) Title: OBSERVATION SYSTEM

(57) Abstract

In an observation system, comprising an observation camera (A, B, C, D), and an observation monitor unit (CU, M) coupled to the observation camera (A, B, C, D), upon the occurrence of a for observation purposes relevant event (doorbell DB) a plurality of preferably sub-sampled images including an image at a time of the event are recorded and a sequence (E) formed by the plurality of images is repeatedly displayed.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Observation system.

The invention relates to an observation system, and to an observation monitor.

In prior art observation systems, a plurality of observation cameras (e.g. 4) are
5 connected to a single observation monitor. Possibly, it is even possible to display ordinary television signals on the observation monitor. Most of the times, nothing happens on the monitor screen, so that the guard gets bored and does other things such as reading a book or a magazine, or watching a football game. It is thus possible that important events are missed.

10 It is, *inter alia*, an object of the invention to provide an observation system and an observation monitor which do not suffer from the above-mentioned disadvantage. To this end, a first aspect of the invention provides an observation system as defined by claim 1. A second aspect of the invention provides a method of observing a complex as defined by
15 claim 5. A third aspect of the invention provides an observation monitor control unit as defined by claim 6. Advantageous embodiments are defined in the dependent claims.

In an observation system in accordance with a primary aspect of the present invention, comprising an observation camera and an observation monitor unit coupled to the observation camera, upon the occurrence of a for observation purposes relevant event (e.g. a
20 ringing doorbell) a plurality of preferably sub-sampled images including an image at a time of the event are recorded and a sequence formed by the plurality of images is repeatedly displayed.

The invention solves the mentioned problem that relevant events may be missed, in that a for observation purposes relevant event is detected, and a sequence of
25 images including an image at the time of that event is repeatedly replayed on an observation monitor. This will draw the guard's attention, so that appropriate action is taken. The event may, for example, be a doorbell, a cable cut, an alarm contact, or a movement detection.

Preferably, the displayed image sequence includes images preceding the event. If 8 seconds are stored at a 2 frames per second rate, the sequence preferably comprises 4

seconds before and 4 seconds after the event.

Advantageously, the sequence is displayed in PIP form, which is a more attention-drawing format and which needs less storage memory.

Preferably, in the case of multiple events, a sequence including a latest of the
5 multiple events is repeatedly displayed.

These and other aspects of the invention will be apparent from and elucidated with reference to the embodiments described hereinafter.

10 The drawing shows an embodiment of an observation system in accordance with the present invention

In the drawing, four cameras A, B, C, D are coupled to a control unit CU. The
15 control unit CU may further receive an antenna signal from an antenna AN thru a tuner (not shown) to allow the guards to watch a football game or something like that. In accordance with the present invention, the control unit CU also receives a doorbell signal from a doorbell DB, an alarm signal from a wire cut detector WCD detecting whether a wire W is cut, and/or a movement detection signal from a movement detector (not shown). In this
20 embodiment, it is supposed that camera A watches the doorbell DB, while camera B watches the wire W. An output of the control unit CU is coupled to a monitor M for displaying the camera signals A, B, C, D (all four together or a selected one of them), or the football match from the antenna AN.

If the doorbell DB is pressed (or some other for observation purposes relevant
25 event occurs), the control unit CU stores a small sequence of images (e.g. 16 images at a rate of 2 images per second), preferably half of which precedes the doorbell-pressing action and half of which follows the doorbell-pressing action. This is possible if the images from the cameras are continuously applied to a storage unit (not shown) and stored upon activation of the doorbell DB or upon some other activity, or if the images of the cameras are
30 continuously spatially and temporally subsampled and delayed, and stored immediately upon receipt of an alarm. The delayed signal is then stored and will show some seconds preceding the alarm as well as some seconds following the alarm. The subsampled images are shown in a picture-in-picture (PIP) window E on the display screen of the monitor M. Preferably, a known photo-finish PIP IC or IC set is used for this purpose. While in the drawing, the PIP

image E is shown inserted into image B from camera B among images A, C, D from cameras A, C, D, it is also possible that image E pops up while a football match is shown on the monitor M, or that the monitor M automatically switches over from displaying images received by the antenna AN to (one of) the camera images A, B, C, D with PIP image E
5 repeatedly showing the relevant event.

A practical embodiment is briefly summarized as follows. The invention can be applied in a low-cost black and white observation system. In this observation system there will be an event replay (store and replay) function. If there is an event (doorbell or alarm)
10 then the observation system stores 4 seconds before the event and 4 seconds after the event in a PIP memory. In case of a cable cut disconnecting a camera from the control unit, the last 8 eight seconds before the event occurs, will be stored. During storage of the frames it will display at the same time the frames, in a small (1/8 size) PIP in the right top corner of the screen, in a sequential loop, the stored frames. The displaying speed is at the store
15 sample rate. If there is an event, this replay function will be started automatically after detecting such an event. In case of multiple events on multiple cameras, the system will always switch to the camera corresponding to the latest event, and this latest event will be stored and replayed. The replay function starts with the oldest stored frame. In 50 and 60 Hz systems the number of stored frames is 16.


20 It should be noted that the above-mentioned embodiments illustrate rather than limit the invention, and that those skilled in the art will be able to design many alternative embodiments without departing from the scope of the appended claims. In the claims, any reference signs placed between parentheses shall not be construed as limiting the claim. The
25 word "comprising" does not exclude the presence of other elements than those listed in a claim. The invention can be implemented by means of hardware comprising several distinct elements, and by means of a suitably programmed computer. In the device claim enumerating several means, several of these means can be embodied by one and the same item of hardware. Where the claim mentions an observation camera and an observation
30 monitor, several of these cameras and/or monitors may be present in the observation system. The sequence can be displayed temporally subsequently in one PIP section E on the display, or as e.g. 16 small pictures spatially adjacent to each other. The control unit CU and the monitor M may be included in one apparatus, or may be sold as separate units as shown in the drawing.

Claims:

1. An observation system, comprising:
an observation camera (A, B, C, D); and
an observation monitor unit (CU, M) coupled to said observation camera (A, B, C, D); characterized by:
5 means (DB, WCD) for detecting a for observation purposes relevant event; and
wherein
said observation monitor unit (CU, M) comprises:
recording means (REC) for recording a plurality of images including an image
at a time of said event;
10 means (M) for repeatedly displaying a sequence (E) formed by said plurality of
images upon said event.
2. An observation system as claimed in claim 1, wherein said plurality of images
includes images preceding said event.
15
3. An observation system as claimed in claim 1, wherein said sequence is
displayed in PIP form (E).
4. An observation system as claimed in claim 1, wherein in the case of multiple
20 events, a sequence including a latest of said multiple events is repeatedly displayed.
5. A method of observing a complex, the method including:
using at least one observation camera (A, B, C, D) and an observation monitor
unit (CU, M) coupled to said at least one observation camera (A, B, C, D); characterized
25 by:
detecting (DB, WCD) a for observation purposes relevant event;
(CU) a plurality of images including an image at a time of said event; and
repeatedly displaying (M) a sequence (E) formed by said plurality of images
upon said event.

6. An observation monitor control unit (CU), comprising:
means for receiving camera signals (A, B, C, D);
means for receiving event detection signals (DB, WCD) indicating a for
observation purposes relevant event;
- 5 means (REC) for recording a plurality of sub-sampled images including an
image at a time of said relevant event to repeatedly supply a sequence formed by said
plurality of sub-sampled images.

1/1



INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 99/00777

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04N 7/18, G08B 13/196

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04N, G08B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC, WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	JP 63070683 A (MITSUBISHI ELECTRIC CORP) 1988-03-30 (abstract) Word Patents Index (online). London U.K. Derwent Publication, Ltd. (retrieved on 1999-10-25). Retrieved from: EPO PAJ Database	1-6
	--	
P,A	WO 9826389 A1 (SIDERAL S.R.L.), 18 June 1998 (18.06.98), figures 1-6, abstract	1-6
	--	
A	GB 2226732 A (SAMSUNG ELECTRONICS COMPANY LIMITED), 4 July 1990 (04.07.90), claims 1,3, abstract	1-6
	--	

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

26 October 1999

Date of mailing of the international search report

28-10-1999

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Anders Brinkman / MR

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 99/00777

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2296150 A (S.J. TONKS), 19 June 1996 (19.06.96), figures 1-4, abstract --	1-6
P,X	GB 2326049 A (E. TAYLOR), 9 December 1998 (09.12.98), abstract --	1-6
A	JP 63269874 A (SAIBAATEC KK) 1998-11-08 (abstract) World Patents Index (online). London U.K.: Derwent Publications, Ltd. (retrieved on 1999-10-25) Retrieved from: EPO PAJ Database --	1-6
A	US 4630110 A (R.E. COTTON ET AL), 16 December 1986 (16.12.86), figures 1-3, abstract -- -----	1-6

INTERNATIONAL SEARCH REPORT

Information on patent family members


International application No.

PCT/IB 99/00777

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
WO	9826389	A1	18/06/98	AU	2229497 A	03/07/98
				IT	MI962573 A	09/06/98
GB	2226732	A	04/07/90	DE	3923361 A,C	12/07/90
GB	2296150	A	19/06/96	GB	9425512 D	00/00/00
GB	2326049	A	09/12/98	GB	9809965 D	00/00/00
US	4630110	A	16/12/86	NONE		

THIS PAGE BLANK (USPTO)

1/1



THIS PAGE BLANK (USE)